

LIST OF CERTIFIED CONVEYOR BELTING

(List updated as of June 2023)

IMPORTANT REMARKS2

DISCLAIMER3

CSA-M422-Type A1.....4

CSA-M422-Type A2..... 14

CSA-M422-Type B1A..... 17

CSA-M422-Type B1B..... 17

CSA-M422-Type B2..... 17

CSA-M422-Type C..... 18

The following Remarks and Disclaimer are important parts of each report:

IMPORTANT REMARKS

1. This report remains valid for five years from the date on which it was signed. The report becomes invalid if the activities and/or categories tested are changed and/or a newer standard become available.
2. Test results contained in this report apply to those samples that were tested and may not be indicative of the total product from which the samples were drawn, or other manufactured batches of this type of product.
3. These test results on their own do not indicate the fire hazard of the tested materials under actual fire conditions and consequently, should not be applied to the assessment of fire hazard without taking into account additional supportive information.
4. Some information presented in this report has been provided by the applicant, and is not subjected to verification by the undersigned. Example: product description, trade name, color, dimensions, thickness, strength, configuration, base material, other components.
5. All conveyor belting being supplied for use shall be initially and periodically type tested to independently confirm the conveyor belting complies and remain in compliance with the standard. As a minimum, but not limited to, type testing shall be carried out:
 - A. Before any belting construction is supplied for use on the first occasion;
 - B. At least every 5 years;
 - C. Where the conveyor belt is to be manufactured at an alternative factory;
 - D. Where there is a change in supply of raw materials that may affect the performance;
 - E. Where there is a change or difference in the manufacturing process, which may affect the performance; and

F. Where the manufacturer/supplier/end user becomes aware of circumstances where product has been supplied and subsequently found to be non-compliant to this standard.

(Modified from AS 4606-2012)

DISCLAIMER

The undersigned has made every attempt to ensure the accuracy and reliability of the information provided in this report. However, the information is provided "as is" without warranty of any kind. The undersigned does not accept any responsibility or liability for the accuracy, content, completeness, legality, or reliability of the information contained in this report. No warranties, promises and/or representations of any kind, expressed or implied, are given as to the nature, standard, accuracy or otherwise of the information provided in this report nor to the suitability or otherwise of the information to your particular circumstances. We shall not be liable for any loss or damage of whatever nature (direct, indirect, consequential, or other) whether arising in contract, tort or otherwise, which may arise as a result of your use of (or failure to use) the information in this report. No part of this report resulting from an investigation into performance of materials may be used in any suit or action for damages arising out of any matter mentioned in such report.

CSA-M422-Type A1

Report #: A1027-CSA M422-14-BELT A1-2023-01

Fenner Dunlop ECS | 700 Ecclestone Drive, Bracsebridge, Canada

DATE: Valid till March 12, 2028

Item #1: Fenner FR6500DE

Trade name	: Fenner
Belt Style	: FR6500DE
Textile	: Solid woven Polyester & Nylon
Top/Carry cover compound	: FR PVC - 1
Bottom/Pulley cover compound	: FR PVC - 1
Between Plies Material	: No.1 PVC
Carry cover thickness	: 1.2 mm
Pulley Cover thickness	: 1.2 mm
Textile Gauge	: 7.7 mm (± 1.5 mm)
Nominal total thickness	: 10.5 mm
Country of Origin/ Production Facility Location	: India / Madurai

XX

REPORT #: A1025-CSA M422-14-BELT A1-2022-07**International Conveyors Limited | E-39, MIDC Chikalthana, Aurangabad 431006, Maharashtra, India**

DATE: Valid till December 8, 2027

Item # 1 : ICL MINEPLAST PVC TYPE - 5000

Trade name	: ICL MINEPLAST
Belt Style	: TYPE-5000
Top/carry cover compound	: PVC (CP-16)
Skim compound	: NA
Bottom/pulley cover compound	: PVC (CP-16)
Fabric	: SOLID WOVEN (Polyester / Nylon / Cotton)
Carry cover thickness	: 1.5 mm
Pulley Cover thickness	: 1.5 mm
Nominal Carcass Thickness	: NA
Nominal total thickness	: Max = 11.8 mm Min = 11.0 mm Ave = 11.6 mm
Country of Origin/ Production Facility Location	: India, Aurangabad

Item # 2 : ICL MINEPLAST PVC TYPE - 10000

Trade name	: ICL MINEPLAST
Belt Style	: TYPE-10000
Top/carry cover compound	: PVC (CP-16)
Skim compound	: NA
Bottom/pulley cover compound	: PVC (CP-16)
Fabric	: SOLID WOVEN (Polyester / Nylon / Cotton)
Carry cover thickness	: 1.5 mm
Pulley Cover thickness	: 1.5 mm
Nominal Carcass Thickness	: NA
Nominal total thickness	: Max = 15.8 mm Min = 15.5 mm Ave = 15.6 mm
Country of Origin/ Production Facility Location	: India, Aurangabad

Item # 3 : ICL MINEPLAST PVC TYPE - 18000

Trade name	: ICL MINEPLAST
Belt Style	: TYPE-18000
Top/carry cover compound	: PVC (CP-16)
Skim compound	: NA
Bottom/pulley cover compound	: PVC (CP-16)
Fabric	: SOLID WOVEN (Polyester / Nylon / Cotton)
Carry cover thickness	: 1.5 mm
Pulley Cover thickness	: 1.5 mm
Nominal Carcass Thickness	: NA
Nominal total thickness	: Max = 20.1 mm Min = 19.7 mm Ave = 20.0 mm
Country of Origin/ Production Facility Location	: India, Aurangabad

Item # 4 : ICL MINEPLAST PVC TYPE - 6500

Trade name	: ICL MINEPLAST
Belt Style	: TYPE-6500
Top/carry cover compound	: PVC (CP-16)
Skim compound	: NA
Bottom/pulley cover compound	: PVC (CP-16)
Fabric	: SOLID WOVEN (Polyester / Nylon / Cotton)
Carry cover thickness	: 1.5 mm
Pulley Cover thickness	: 1.5 mm
Nominal Carcass Thickness	: NA
Nominal total thickness	: Max = 11.2 mm Min = 10.8 mm Ave = 11.0 mm
Country of Origin/ Production Facility Location	: India, Falta

Item # 5 : ICL MINEPLAST PVC TYPE - 12000

Trade name	: ICL MINEPLAST
Belt Style	: TYPE-12000
Top/carry cover compound	: PVC (CP-16)
Skim compound	: NA
Bottom/pulley cover compound	: PVC (CP-16)
Fabric	: SOLID WOVEN (Polyester / Nylon / Cotton)
Carry cover thickness	: 1.5 mm
Pulley Cover thickness	: 1.5 mm
Nominal Carcass Thickness	: NA
Nominal total thickness	: Max = 15.7 mm Min = 15.3 mm Ave = 15.5 mm
Country of Origin/ Production Facility Location	: India, Falta

[illegible]

REPORT #: A1023-CSA M422-14 (R2019)-BELT A1-2022-01

Indica Conveyors Limited | Fatehgarh Shukar Chuk Road, Verka, Amritsar – 143501, India

DATE: Valid till August 17, 2027

Item # 1: ORBIT PLAST TYPE - 8000

Trade name	: ORBIT PLAST
Belt Style	: TYPE-8000
Top/carry cover compound	: PVC Cover Compound (CC-01/A1)
Skim compound	: PVC Impregnation Compound (IC-01/A1)
Bottom/pulley cover compound	: PVC Cover Compound (CC-01/A1)
Fabric	: Solid Woven (Polyester/Nylon/Cotton)
Carry cover thickness	: 1.5 mm
Pulley Cover thickness	: 1.5 mm
Nominal Carcass Thickness	: 9.5 mm
Nominal total thickness	: 13.55 mm (Av.) 13.6 mm (Max) 13.5 (Min)
Country of Origin/ Production Facility Location	: India, Amritsar

XX

REPORT #: A1022-CSA M422-14 (R2019)-BELT A1-2021-08

Indica Conveyors Limited | Fatehgarh Shukar Chuk Road, Verka, Amritsar – 143501, India

DATE: Valid till Dec 21, 2026

Item # 1: ORBIT PLAST TYPE - 12000

Trade name	: ORBIT PLAST
Belt Style	: TYPE-12000
Top/carry cover compound	: PVC Cover Compound (CC-01/A1)
Skim compound	: PVC Impregnation Compound (IC-01/A1)
Bottom/pulley cover compound	: PVC Cover Compound (CC-01/A1)
Fabric	: Solid Woven (Polyester/Nylon/Cotton)
Carry cover thickness	: 1.5 mm
Pulley Cover thickness	: 1.5 mm
Nominal Carcass Thickness	: 11.5 mm
Nominal total thickness	: Min 14.4 Max 14.53 Average 14.44 mm (Measured)
Country of Origin/ Production Facility Location	: India, Amritsar

[illegible]

REPORT # A1019-CSA M422-14-BELT A1-2019-12**FENNER DUNLOP ECS | Marfleet, Hull HU9 5RA, UK**

DATE: Valid till Feb 21, 2025

Item #1: FR / KCL 5000 Fenner-Dunlop, Marfleet, Hull, UK

Trade name	: Fenner Dunlop
Belt Style	: FR / KCL 5000
Textile	: Polyester & Nylon
Top/Carry cover compound	: FR PVC
Bottom/Pulley cover compound	: FR PVC
Between Plies Material	: No.1 PVC
Carry cover thickness	: 2 mm
Pulley Cover thickness	: 2 mm
Textile Gauge	: 6.3 mm
Nominal total thickness	: 10.3 mm +/- 1.5 mm
Country of Origin/ Production Facility Location	: UK, Marfleet, Hull

Item #2: FR / KCL 10000 Fenner-Dunlop, Marfleet, Hull, UK

Trade name	: Fenner Dunlop
Belt Style	: FR / KCL 10000
Textile	: Polyester & Nylon
Top/Carry cover compound	: FR PVC
Bottom/Pulley cover compound	: FR PVC
Between Plies Material	: No.1 PVC
Carry cover thickness	: 3 mm
Pulley Cover thickness	: 3 mm
Textile Gauge	: 11 mm
Nominal total thickness	: 17 mm +/- 1.5 mm
Country of Origin/ Production Facility Location	: UK, Marfleet, Hull

Item #3: FR / KCL 15000 Fenner-Dunlop, Marfleet, Hull, UK

Trade name	: Fenner Dunlop
Belt Style	: FR / KCL 15000
Textile	: Polyester & Nylon
Top/Carry cover compound	: FR PVC
Bottom/Pulley cover compound	: FR PVC
Between Plies Material	: No.1 PVC
Carry cover thickness	: 1 mm
Pulley Cover thickness	: 1 mm
Textile Gauge	: 14 mm
Nominal total thickness	: 16 mm +/- 1.5 mm
Country of Origin/ Production Facility Location	: UK, Marfleet, Hull

Item #4: FRSR 10000 Fenner-Dunlop, Marfleet, Hull, UK

Trade name	: Fenner Dunlop
Belt Style	: FRSR 10000
Textile	: Polyester & Nylon
Top/Carry cover compound	: 7022
Bottom/Pulley cover compound	: 5844 (FR PVC)
Between Plies Material	: No.8 PVC
Carry cover thickness	: 3 mm
Pulley Cover thickness	: 3 mm
Textile Gauge	: 10.5 mm
Nominal total thickness	: 16.5 mm +/- 1.5 mm
Country of Origin/ Production Facility Location	: UK, Marfleet, Hull

Item #5: FRSR 15000 Fenner-Dunlop, Marfleet, Hull, UK

Trade name	: Fenner Dunlop
Belt Style	: FRSR 15000
Textile	: Polyester & Nylon
Top/Carry cover compound	: 7022
Bottom/Pulley cover compound	: FR PVC
Between Plies Material	: No.8 PVC
Carry cover thickness	: 2 mm
Pulley Cover thickness	: 0 mm rubber + 1 mm PVC
Textile Gauge	: 14 mm
Nominal total thickness	: 17 mm +/- 1.5 mm
Country of Origin/ Production Facility Location	: UK, Marfleet, Hull

[illegible]

>> End of Section

CSA-M422-Type A2

Report #: A2012-CSA M422-12-BELT A2-2019-11

FENNER DUNLOP ECS | 700 Ecclestone Drive, Bracebridge, Ontario, Canada

Date: Valid till November 20, 2024

Item #1: Fenner-Dunlop Americas Conveyor Belting

Trade name	: Mineflex D18 - D20 Fire Boss CAR
Belt Style	: Textile / Rubber Belt CSA Type A2 compliant
Textile	: 2000/2 piw Polyester/Nylon (0.212" (5.38 mm) x 2 plies)
Top/Carry cover compound	: 1456 Rubber Compound
Bottom/Pulley cover compound	: 1456 Rubber Compound
Between Plies Material	: 1404 Rubber Compound
Carry cover thickness	: 0.250" (6.35 mm)
Pulley Cover thickness	: 0.250" (6.35 mm)
Textile Gauge	: 0.212" (5.38 mm)
Nominal total thickness	: 24.0 mm (Average), 24.3 mm (Max), 23.7 mm (Min)
Country of Origin/ Production Facility Location	: USA (Port Clinton OH)

Note: This belt was tested as per the CSA-M422-12, which is also the CSA-M422-87 (Type A2 Belting). A 2014 edition of the standard is available.

[illegible]

Fenner Dunlop ECS | 700 Ecclestone Drive, Bracebridge, Ontario, Canada

Date: Valid till Dec 1, 2023

Item #1: Fenner-Dunlop Americas Conveyor Belting

Trade name	: Mineflex D15 FB-CAR CSA-A2
Belt Style	: Rubber and Textile construction
Textile	: Usflex D15
Top/Carry cover compound	: 1456
Bottom/Pulley cover compound	: 1456
Skim Compound	: 1404
Carry cover thickness	: 6.4 mm
Pulley Cover thickness	: 6.4 mm
Textile Gauge	: 5.1 mm
Nominal total thickness	: 24.27 mm (Average), 24.49 mm (Max), 24.08 mm (Min)
Country of Origin/ Production Facility Location	: Canada/ Bracebridge

Note: This belt was tested as per the CSA-M422-12, which is also the CSA-M422-87 (Type A2 Belting). A 2014 edition of the standard is available.

~~~~~

>> End of Section



# CSA-M422-Type B1A

None

>> End of Section

# CSA-M422-Type B1B

None

>> End of Section

# CSA-M422-Type B2

None

>> End of Section

# CSA-M422-Type C

**REPORT #: C030-CSA M422-14-BELT C-2023-01**

**Sempertrans Bełchatów Sp. z o. o. | Wola Grzymalina 11, 97-427 Rogowiec, Poland**

DATE: Valid till May 8, 2028

**Item #1: Flextrans EPP 500/1 19.1+9.5 FRC+**

|                                                    |                                                                                     |
|----------------------------------------------------|-------------------------------------------------------------------------------------|
| Trade name                                         | : Flextrans 500/1 19.1+9.5 FRC+                                                     |
| Belt style                                         | : EPP 500/1                                                                         |
| Top/carry cover material                           | : 4787                                                                              |
| Skim/ Cushion material                             | : 4731                                                                              |
| Bottom/pulley cover material                       | : 4787                                                                              |
| Fabric/Textile/Reinforcement                       | : EPP500                                                                            |
| Carry cover thickness                              | : 19.1 mm                                                                           |
| Pulley cover thickness                             | : 9.5 mm                                                                            |
| Cord diameter/construction                         | : N/A                                                                               |
| Textile Gauge/Cord Gauge                           | : Straight Warp Fabric                                                              |
| Nominal total thickness                            | : Ave 31.12 mm   Max 31.22 mm   Min 31.09 mm                                        |
| Country of origin/<br>Production facility location | : Sempertrans Bełchatów Sp. z o. o., Poland,<br>Wola Grzymalina 11, Rogowiec 97-427 |

**Item #2: Flextrans EPP 1000/1 4.8+4.8 FRC+**

|                                                    |                                                                                     |
|----------------------------------------------------|-------------------------------------------------------------------------------------|
| Trade name                                         | : Flextrans 1000/1 4.8+4.8 FRC+                                                     |
| Belt style                                         | : EPP 1000/1                                                                        |
| Top/carry cover material                           | : 4787                                                                              |
| Skim/ Cushion material                             | : 4731                                                                              |
| Bottom/pulley cover material                       | : 4787                                                                              |
| Fabric/Textile/Reinforcement                       | : EPP1000                                                                           |
| Carry cover thickness                              | : 4.8 mm                                                                            |
| Pulley cover thickness                             | : 4.8 mm                                                                            |
| Cord diameter/construction                         | : N/A                                                                               |
| Textile Gauge/Cord Gauge                           | : Straight Warp Fabric                                                              |
| Nominal total thickness                            | : Ave 13.28 mm   Max 13.28 mm   Min 13.26 mm                                        |
| Country of origin/<br>Production facility location | : Sempertrans Bełchatów Sp. z o. o., Poland,<br>Wola Grzymalina 11, Rogowiec 97-427 |

**Item #3: Flextrans EPP 1000/2 19.1+9.5 FRC+**

|                                                    |                                                                                     |
|----------------------------------------------------|-------------------------------------------------------------------------------------|
| Trade name                                         | : Flextrans 1000/2 19.1+9.5 FRC+                                                    |
| Belt style                                         | : EPP 1000/2                                                                        |
| Top/carry cover material                           | : 4787                                                                              |
| Skim/ Cushion material                             | : 4731                                                                              |
| Bottom/pulley cover material                       | : 4787                                                                              |
| Fabric/Textile/Reinforcement                       | : EPP500                                                                            |
| Carry cover thickness                              | : 19.1 mm                                                                           |
| Pulley cover thickness                             | : 9.5 mm                                                                            |
| Cord diameter/construction                         | : N/A                                                                               |
| Textile Gauge/Cord Gauge                           | : Straight Warp Fabric                                                              |
| Nominal total thickness                            | : Ave 34.81 mm   Max 34.93 mm   Min 34.62 mm                                        |
| Country of origin/<br>Production facility location | : Sempertrans Bełchatów Sp. z o. o., Poland,<br>Wola Grzymalina 11, Rogowiec 97-427 |

**Item #4: Flextrans EPP 2000/2 4.8+4.8 FRC+**

|                                                    |                                                                                     |
|----------------------------------------------------|-------------------------------------------------------------------------------------|
| Trade name                                         | : Flextrans 2000/2 4.8+4.8 FRC+                                                     |
| Belt style                                         | : EPP 2000/2                                                                        |
| Top/carry cover material                           | : 4787                                                                              |
| Skim/ Cushion material                             | : 4731                                                                              |
| Bottom/pulley cover material                       | : 4787                                                                              |
| Fabric/Textile/Reinforcement                       | : EPP1000                                                                           |
| Carry cover thickness                              | : 4.8 mm                                                                            |
| Pulley cover thickness                             | : 4.8 mm                                                                            |
| Cord diameter/construction                         | : N/A                                                                               |
| Textile Gauge/Cord Gauge                           | : Straight Warp Fabric                                                              |
| Nominal total thickness                            | : Ave 20.12 mm   Max 20.19 mm   20.02 mm                                            |
| Country of origin/<br>Production facility location | : Sempertrans Bełchatów Sp. z o. o., Poland,<br>Wola Grzymalina 11, Rogowiec 97-427 |

୧୨୩୪୫୬୭୮୯୧୦୧୧୧୨୧୩୧୪୧୫୧୬୧୭୧୮୧୯୨୦୨୧୨୨୨୩୨୪୨୫୨୬୨୭୨୮୨୯୩୦୩୧୩୨୩୩୩୪୩୫୩୬୩୭୩୮୩୯୪୦୪୧୪୨୪୩୪୪୪୫୪୬୪୭୪୮୪୯୫୦୫୧୫୨୫୩୫୪୫୫୫୬୫୭୫୮୫୯୬୦୬୧୬୨୬୩୬୪୬୫୬୬୬୭୬୮୬୯୭୦୭୧୭୨୭୩୭୪୭୫୭୬୭୭୭୮୭୯୮୦୮୧୮୨୮୩୮୪୮୫୮୬୮୭୮୮୮୯୯୦୯୧୯୨୯୩୯୪୯୫୯୬୯୭୯୮୯୯

**REPORT #: C029-CSA M422-14-BELT C-2022-11**

**Sempertrans Bełchatów Sp. z o.o. | Transportowa 5, 97-427 Rogowiec, Poland**

DATE: Valid till December 28, 2027

**Item #1: Sempercord Transflam ST 1600 FRC+**

|                                                    |                                                                                     |
|----------------------------------------------------|-------------------------------------------------------------------------------------|
| Trade name                                         | : Sempercord Transflam ST 1600 FRC+                                                 |
| Belt style                                         | : ST 1600                                                                           |
| Top/carry cover material                           | : 4787                                                                              |
| Skim/ Cushion material                             | : 4775                                                                              |
| Bottom/pulley cover material                       | : 4787                                                                              |
| Fabric/Textile/Reinforcement                       | : Metal cord reinforcement in carry cover (Ø1,55 mm)                                |
| Carry cover thickness                              | : 13.0 mm                                                                           |
| Pulley cover thickness                             | : 6.0 mm                                                                            |
| Cord diameter/construction                         | : N/A                                                                               |
| Textile Gauge/Cord Gauge                           | : Ø5,0 mm / 7x7 Zn                                                                  |
| Nominal total thickness                            | : 26.7 mm (range: 26.7 mm – 26.7 mm   exact )                                       |
| Country of origin/<br>Production facility location | : Sempertrans Bełchatów Sp. z o. o., Poland,<br>Wola Grzymalina 11, Rogowiec 97-427 |

XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX

**REPORT #: C028-CSA M422-14-BELT C-2022-07**

**Sempertrans Bełchatów Sp. z o. o. | Wola Grzymalina 11, 97-427 Rogowiec, Poland**

DATE: Valid till December 28, 2027

**Item #1: Sempercord Transflam ST 500 FRC+**

|                                                    |                                                                                     |
|----------------------------------------------------|-------------------------------------------------------------------------------------|
| Trade name                                         | : Sempercord Transflam ST 500 FRC+                                                  |
| Belt style                                         | : ST 500                                                                            |
| Top/carry cover material                           | : 4787                                                                              |
| Skim/ Cushion material                             | : 4775                                                                              |
| Bottom/pulley cover material                       | : 4787                                                                              |
| Fabric/Textile/Reinforcement                       | : N/A                                                                               |
| Carry cover thickness                              | : 25.4 mm                                                                           |
| Pulley cover thickness                             | : 12.7 mm                                                                           |
| Cord diameter/construction                         | : N/A                                                                               |
| Textile Gauge/Cord Gauge                           | : Ø3.2 mm / 7x7 Zn                                                                  |
| Nominal total thickness                            | : 38.8 mm – 39.3 mm                                                                 |
| Country of origin/<br>Production facility location | : Sempertrans Bełchatów Sp. z o. o., Poland,<br>Wola Grzymalina 11, Rogowiec 97-427 |

XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX

**Item #2: Sempercord Transflam ST 1000 FRC+**

|                                                    |                                                                                     |
|----------------------------------------------------|-------------------------------------------------------------------------------------|
| Trade name                                         | : Sempercord Transflam ST 1000 FRC+                                                 |
| Belt style                                         | : ST 1000                                                                           |
| Top/carry cover material                           | : 4787                                                                              |
| Skim/ Cushion material                             | : 4775                                                                              |
| Bottom/pulley cover material                       | : 4787                                                                              |
| Fabric/Textile/Reinforcement                       | : N/A                                                                               |
| Carry cover thickness                              | : 10.0 mm                                                                           |
| Pulley cover thickness                             | : 8.0 mm                                                                            |
| Cord diameter/construction                         | : N/A                                                                               |
| Textile Gauge/Cord Gauge                           | : Ø3.7 mm / 7x7 Zn                                                                  |
| Nominal total thickness                            | : 22.3 mm   Exact                                                                   |
| Country of origin/<br>Production facility location | : Sempertrans Bełchatów Sp. z o. o., Poland,<br>Wola Grzymalina 11, Rogowiec 97-427 |

**Item #3: Sempercord Transflam ST 2000 FRC+**

|                                                    |                                                                                     |
|----------------------------------------------------|-------------------------------------------------------------------------------------|
| Trade name                                         | : Sempercord Transflam ST 2000 FRC+                                                 |
| Belt style                                         | : ST 2000                                                                           |
| Top/carry cover material                           | : 4787                                                                              |
| Skim/ Cushion material                             | : 4775                                                                              |
| Bottom/pulley cover material                       | : 4787                                                                              |
| Fabric/Textile/Reinforcement                       | : N/A                                                                               |
| Carry cover thickness                              | : 10.0 mm                                                                           |
| Pulley cover thickness                             | : 8.0 mm                                                                            |
| Cord diameter/construction                         | : N/A                                                                               |
| Textile Gauge/Cord Gauge                           | : Ø5.2 mm / 7x7 Zn                                                                  |
| Nominal total thickness                            | : 24.4 mm   exact                                                                   |
| Country of origin/<br>Production facility location | : Sempertrans Bełchatów Sp. z o. o., Poland,<br>Wola Grzymalina 11, Rogowiec 97-427 |



**Item #4: Sempercord Transflam ST 4000 FRC+**

|                                                    |                                                                                     |
|----------------------------------------------------|-------------------------------------------------------------------------------------|
| Trade name                                         | : Sempercord Transflam ST 4000 FRC+                                                 |
| Belt style                                         | : ST 4000                                                                           |
| Top/carry cover material                           | : 4787                                                                              |
| Skim/ Cushion material                             | : 4775                                                                              |
| Bottom/pulley cover material                       | : 4787                                                                              |
| Fabric/Textile/Reinforcement                       | : N/A                                                                               |
| Carry cover thickness                              | : 10.0 mm                                                                           |
| Pulley cover thickness                             | : 8.0 mm                                                                            |
| Cord diameter/construction                         | : N/A                                                                               |
| Textile Gauge/Cord Gauge                           | : Ø8.8 mm / 7x19 Zn                                                                 |
| Nominal total thickness                            | : 27.7   exact                                                                      |
| Country of origin/<br>Production facility location | : Sempertrans Bełchatów Sp. z o. o., Poland,<br>Wola Grzymalina 11, Rogowiec 97-427 |

**Item #5: Sempercord Transflam ST 8000 FRC+**

|                                                    |                                                                                     |
|----------------------------------------------------|-------------------------------------------------------------------------------------|
| Trade name                                         | : Sempercord Transflam ST 8000 FRC+                                                 |
| Belt style                                         | : ST 8000                                                                           |
| Top/carry cover material                           | : 4787                                                                              |
| Skim/ Cushion material                             | : 4775                                                                              |
| Bottom/pulley cover material                       | : 4787                                                                              |
| Fabric/Textile/Reinforcement                       | : N/A                                                                               |
| Carry cover thickness                              | : 6.4 mm                                                                            |
| Pulley cover thickness                             | : 6.4 mm                                                                            |
| Cord diameter/construction                         | : N/A                                                                               |
| Textile Gauge/Cord Gauge                           | : Ø13.5 mm / 7x19 Zn                                                                |
| Nominal total thickness                            | : 26.7 mm   exact                                                                   |
| Country of origin/<br>Production facility location | : Sempertrans Bełchatów Sp. z o. o., Poland,<br>Wola Grzymalina 11, Rogowiec 97-427 |

~~~~~

REPORT #: C027-CSA M422-14-BELT C-2021-12

Fenner Dunlop ECS | 700 Ecclestone Drive, PO Box #2230, Bracebridge, Ontario P1L 1W1 Canada

DATE: Valid till December 11, 2026

Item # 1: Mineflex D20 Fireboss CSA C AR

Trade name	: Mineflex D20 Fireboss CSA C AR
Belt style	: 1000 piw x 2 ply
Top/carry cover material	: 5746
Skim/ Cushion material	: 5619
Bottom/pulley cover material	: 5746
Fabric/Textile	: Polyester & Nylon
Carry cover thickness	: 1/4"
Pulley cover thickness	: 1/8"
Textile Gauge	: 0.212"
Cord Gauge	: NA
Nominal total thickness	: 0.835"
Country of origin/ Production facility location	: Canada (Bracebridge ON)

[illegible]

REPORT #: C026-CSA M422-14-BELT C-2020-08**Fenner Dunlop ECS | 700 Ecclestone Drive, PO Box #2230, Bracebridge, Ontario P1L 1W1 Canada**

DATE: Valid till December 23, 2025

Item # 1: MineHaul Supreme 5-2500 Fire Boss CSA-C OR

Trade name	: MineHaul Supreme 5-2500 Fire Boss CSA-C OR
Belt style	: 500 piw x 5 ply
Top/carry cover material	: 5752
Skim/ Cushion material	: 5619
Bottom/pulley cover material	: 5752
Fabric/Textile	: Polyester & Nylon
Carry cover thickness	: 1/16"
Pulley cover thickness	: 1/16"
Textile Gauge	: 0.122"
Cord Gauge	: NA
Nominal total thickness	: 0.897" (range: 0.905" – 0.885")
Country of origin/ Production facility location	: Canada (Bracebridge ON)

Item # 2: Mineflex D15 Fire Boss CSA-C OR

Trade name	: Mineflex D15 Fire Boss CSA-C OR
Belt style	: 750 piw x 2 ply
Top/carry cover material	: 5752
Skim/ Cushion material	: 5619
Bottom/pulley cover material	: 5752
Fabric/Textile	: Polyester & Nylon
Carry cover thickness	: 1/2"
Pulley cover thickness	: 1/4"
Textile Gauge	: 0.201"
Cord Gauge	: NA
Nominal total thickness	: 1.191" (range: 1.22" – 1.152")
Country of origin/ Production facility location	: Canada (Bracebridge ON)

Item # 3: MineHaul Supreme 4-800 Fire Boss CSA-C OR

Trade name	: MineHaul Supreme 4-800 Fire Boss CSA-C OR 1/8x1/8
Belt style	: 200 piw x 4 ply
Top/carry cover material	: 5752
Skim/ Cushion material	: 5619
Bottom/pulley cover material	: 5752
Fabric/Textile	: Polyester & Nylon
Carry cover thickness	: 1/8"
Pulley cover thickness	: 1/8"
Textile Gauge	: 0.061"
Cord Gauge	: NA
Nominal total thickness	: 0.592" (range: 0.598" – 0.584")
Country of origin/ Production facility location	: Canada (Bracebridge ON)

Item # 4: MineHaul Supreme 2-220 Fire Boss CSA-C OR

Trade name	: MineHaul Supreme 2-220 Fire Boss CSA-C OR
Belt style	: 110 piw x 2 ply
Top/carry cover material	: 5752
Skim/ Cushion material	: 5619
Bottom/pulley cover material	: 5752
Fabric/Textile	: Polyester & Nylon
Carry cover thickness	: 1"
Pulley cover thickness	: 1/2"
Textile Gauge	: 0.030"
Cord Gauge	: NA
Nominal total thickness	: 1.685" (range: 1.725" – 1.6")
Country of origin/ Production facility location	: Canada (Bracebridge ON)

[illegible]

REPORT #: C025-CSA M422-14-BELT C-2020-08

Sempertrans Bełchatów Sp. z o.o. | Transportowa 5, 97-427 Rogowiec, Poland

DATE: Valid till September 24, 2025

Item #1: Multitrans Transflam EP 630/3 12.7 + 6.4 FRC+

Trade name	: Multitrans Transflam EP 630/3 FRC+
Belt style	: EP 630/3
Top/carry cover material	: 4787
Skim/ Cushion material	: 4731
Bottom/pulley cover material	: 4787
Fabric/Textile	: EP200N
Carry cover thickness	: 12.7 mm
Pulley cover thickness	: 6.4 mm
Cord diameter/construction	: N/A
Textile Gauge	: Fabric Polyester/Polyamide
Nominal total thickness	: 21.6 mm (range: 21.5 mm – 21.7 mm)
Country of origin/ Production facility location	: Poland / Sempertrans Bełchatów Sp. Z o. o. Rogowiec 97-427, ul. Transportowa 5

Item #2: Multitrans Transflam EP 1250/5 6.4 + 3.2 FRC+

Trade name	: Multitrans Transflam EP 1250/5 FRC+
Belt style	: EP 1250/5
Top/carry cover material	: 4787
Skim/ Cushion material	: 4731
Bottom/pulley cover material	: 4702
Fabric/Textile	: EP250N
Carry cover thickness	: 6.4 mm
Pulley cover thickness	: 3.2 mm
Cord diameter/construction	: N/A
Textile Gauge	: Fabric Polyester/Polyamide
Nominal total thickness	: 18.37 mm (range: 18.2 mm – 18.5 mm)
Country of origin/ Production facility location	: Poland / Sempertrans Bełchatów Sp. Z o. o. Rogowiec 97-427, ul. Transportowa 5

Item #3: Multitrans Transflam EP 1800/4 4.8 + 1.6 FRC+

Trade name	: Multitrans Transflam EP 1800/4 FRC+
Belt style	: EP 1800/4
Top/carry cover material	: 4787
Skim/ Cushion material	: 4731
Bottom/pulley cover material	: 4702
Fabric/Textile	: EP400N
Carry cover thickness	: 4.8 mm
Pulley cover thickness	: 1.6 mm
Cord diameter/construction	: N/A
Textile Gauge	: Fabric Polyester/Polyamide
Nominal total thickness	: 15.24 mm (range: 15.06 mm – 15.4 mm)
Country of origin/ Production facility location	: Poland / Sempertrans Bełchatów Sp. Z o. o. Rogowiec 97-427, ul. Transportowa 5

୧୨୩୪୫୬୭୮୯୧୦୧୧୧୨୧୩୧୪୧୫୧୬୧୭୧୮୧୯୨୦୨୧୨୨୨୩୨୪୨୫୨୬୨୭୨୮୨୯୩୦୩୧୩୨୩୩୩୪୩୫୩୬୩୭୩୮୩୯୪୦୪୧୪୨୪୩୪୪୪୫୪୬୪୭୪୮୪୯୫୦୫୧୫୨୫୩୫୪୫୫୫୬୫୭୫୮୫୯୬୦୬୧୬୨୬୩୬୪୬୫୬୬୬୭୬୮୬୯୭୦୭୧୭୨୭୩୭୪୭୫୭୬୭୭୭୮୭୯୮୦୮୧୮୨୮୩୮୪୮୫୮୬୮୭୮୮୮୯୯୦୯୧୯୨୯୩୯୪୯୫୯୬୯୭୯୮୯୯

REPORT #: C024-CSA M422-14-BELT C-2019-08

2k-belting GmbH | Bergstraße 46, 2102 Hagenbrunn Austria

DATE: Valid till December 30, 2024

Item #1: 2K PVC 1250S 2.5 + 2.5 CSA C

Trade name	: 2K PVC 1250S 2.5 + 2.5 CSA C
Belt style	: PVC 1250S
Top/carry cover material	: 25265-19-4 & 9003-18-3 (Cas No.)
Between Plies material	: 9002-86-2 (Cas No.)
Bottom/pulley cover material	: 25265-19-4 & 9003-18-3 (Cas No.)
Fabric/Textile	: Polyester Nylon, Solid Woven
Carry cover thickness	: 2.5 mm
Pulley cover thickness	: 2.5 mm
Cord diameter/construction	: NA
Textile Gauge	: 8.7 mm
Nominal total thickness	: 13.1 mm average – 13.2 mm max – 13.0 mm min
Country of origin/ Production facility location	: China / No. 1 CGR District, Jiaxiang, Jinan City, Shandong Province

[illegible]

REPORT #: C023-CSA M422-14-BELT C-2019-05

Sempertrans Bełchatów Sp. z o.o. | Transportowa 5, 97-427 Rogowiec, Poland

DATE: Valid till May 21, 2024

Item #1: Sempercord Transflam ST4000 10+8 FRC+

Trade name	: Sempercord Transflam ST4000 FRC+
Belt style	: ST4000
Top/carry cover material	: 4787
Skim/ Cushion material	: 4775
Bottom/pulley cover material	: 4787
Fabric/Textile	: N/A
Carry cover thickness	: 10.0 mm
Pulley cover thickness	: 8.0 mm
Cord diameter/construction	: Ø8,6 mm / 7x19 Zn
Textile Gauge	: N/A
Nominal total thickness	: 26.53 mm average - 26.66 mm max – 26.39 mm min
Country of origin/ Production facility location	: Poland / Sempertrans Bełchatów Rogowiec 97-427, ul. Transportowa 5

Item # 2: Sempercord Transflam ST3150 15+6 FRC+

Trade name	: Sempercord Transflam ST3150 FRC+
Belt style	: ST3150
Top/carry cover material	: 4787
Skim/ Cushion material	: 4775
Bottom/pulley cover material	: 4787
Fabric/Textile	: N/A
Carry cover thickness	: 15.0 mm
Pulley cover thickness	: 6.0 mm
Cord diameter/construction	: Ø7,6 mm / 7x19 Zn
Textile Gauge	: N/A
Nominal total thickness	: 28.80 mm average - 28.71 mm max – 28.98 mm min
Country of origin/ Production facility location	: Poland / Sempertrans Bełchatów Rogowiec 97-427, ul. Transportowa 5

[illegible]

REPORT #: C022-CSA M422-14-BELT C-2018-10

Phoenix CBS GmbH | Gustav-Töpfer-Straße 4, 07422 Bad Blankenburg, Germany

DATE: Valid till Oct 23, 2023

Item # 1: TxFG CSA C

Trade name	: TxFG CSA C
Belt style	: EP2000/5
Top/carry cover material	: 5070
Skim/ Cushion material	: 4915
Bottom/pulley cover material	: 5070
Fabric/Textile	: 5 x EP400
Carry cover thickness	: 9.5 ± 0.2 mm
Pulley cover thickness	: 6.0 ± 0.2 mm
Textile Gauge	: 10.2 ± 0.2 mm
Nominal total thickness	: 26.1 mm (Max 27 mm, Min 25 mm)
Country of origin/ Production facility location	: Germany (Bad Blankenburg)

[illegible]

REPORT #: C021-CSA M422-14-BELT C-2018-06

Fenner Dunlop ECS | 700 Ecclestone Drive, PO Box #2230, Bracebridge, Ontario P1L 1W1 Canada

DATE: Valid till Sep 5, 2023

Item # 1: Fenner-Dunlop Americas Conveyor Belting

Trade name	: Dynaflight FFAR CSA-C – 7.6 mm cord w/breaker
Belt style	: Steel Cord
Top/carry cover material	: 5746
Skim/ Cushion material	: 3024
Bottom/pulley cover material	: 5746
Fabric/Textile	: B120NN breaker
Carry cover thickness	: 6.4 mm
Pulley cover thickness	: 6.4 mm
Textile Gauge	: 2.0 mm
Cord Gage	: 7.6 mm
Nominal total thickness	: 20.7 mm – 21.3 mm
Country of origin/ Production facility location	: Canada (Bracebridge ON)

[illegible]

REPORT #: C020-CSA M422-14-BELT C-2018-06

Fenner-Dunlop Americas Conveyor Belting | 700 Ecclestone Drive, PO Box #2230, Bracebridge, Ontario P1L 1W1 Canada

DATE: Valid till Sep 2, 2023

Item # 1: Fenner-Dunlop Americas Conveyor Belting

Trade name	: Dynaflight FFAR CSA-C – 3.6 mm cord
Belt style	: Steel Cord
Top/carry cover material	: 5746
Skim/ Cushion material	: 3024
Bottom/pulley cover material	: 5746
Fabric/Textile	: none
Carry cover thickness	: 5.0 mm
Pulley cover thickness	: 5.0 mm
Textile Gauge	: None
Cord Gage	: 3.6 mm
Nominal total thickness	: 13.6 mm
Country of origin/ Production facility location	: Canada (Bracebridge ON)

Item # 2: Fenner-Dunlop Americas Conveyor Belting

Trade name	: Dynaflight FFAR CSA-C – 7.6 mm cord w/breaker (B120)
Belt style	: Steel Cord
Top/carry cover material	: 5746
Skim/ Cushion material	: 3024
Bottom/pulley cover material	: 5746
Fabric/Textile	: B120NN breaker
Carry cover thickness	: 6.4 mm
Pulley cover thickness	: 6.4 mm
Textile Gauge	: 2.0 mm
Cord Gage	: 7.6 mm
Nominal total thickness	: 20.7 mm – 21.3 mm
Country of origin/ Production facility location	: Canada (Bracebridge ON)

Item # 3: Fenner-Dunlop Americas Conveyor Belting

Trade name	: Dynaflight FFAR CSA-C – 13.0 mm cord
Belt style	: Steel Cord
Top/carry cover material	: 5746
Skim/ Cushion material	: 3024
Bottom/pulley cover material	: 5746
Fabric/Textile	: none
Carry cover thickness	: 5.0 mm
Pulley cover thickness	: 5.0 mm
Textile Gauge	: None
Cord Gage	: 13.0 mm
Nominal total thickness	: 23.0 mm
Country of origin/ Production facility location	: Canada (Bracebridge ON)

[illegible]

REPORT #: C019-CSA M422-14-BELT C-2018-04

DUNLOP INDUSTRIAL PRODUCTS (Pty) Ltd, Divisions: Belting, Mixing, ORM & Hose | Lincoln Road, Industrial Sites, Private Bag X027, Benoni 1500, South Africa

DATE: Valid till Jul 1, 2023

Item # 1

Trade name	: Dunlop Belting Products 1050S x 4.8 + 1.6
Belt style	: Solid Woven Monoply
Top/carry cover material	: 2269 D01 CR
Skim/ Cushion material	: PVC Impregnation Solution
Bottom/pulley cover material	: 2269 D01 - CR
Fabric/Textile	: Polyester & Poly Cotton
Carry cover thickness	: 4.8 mm
Pulley cover thickness	: 1.6 mm
Textile Gauge	: 0.8 To 1.2mm
Nominal total thickness	: Max=13.2 mm.; Min=13.0 mm, Av.=13.1 mm
Country of origin/ Production facility location	: Benoni, Gauteng, Republic of South Africa

Item # 2:

Trade name	: Dunlop Belting Products 1400S x 4.8 + 1.6
Belt style	: Solid Woven Monoply
Top/carry cover material	: 2269 D01 CR
Skim/ Cushion material	: PVC Impregnation Solution
Bottom/pulley cover material	: 2269 D01 - CR
Fabric/Textile	: Polyester & Poly Cotton
Carry cover thickness	: 4.8mm
Pulley cover thickness	: 1.6mm
Textile Gauge	: 10.8 To 1.2mm
Nominal total thickness	: Max=13.6 mm.; Min=13.2 mm, Av.=13.4 mm
Country of origin/ Production facility location	: Benoni, Gauteng, Republic of South Africa

~~~~~

~~~~~

~~~~~

>> End of Section

>> Update by:

Ehab Zalok, Ph.D., P.Eng.

Professor, Carleton University

Telephone: 1 (613) 520 2600 x 7450

[ehab.zalok@carleton.ca](mailto:ehab.zalok@carleton.ca)

>> End of Document